


	INTAKE	EXHAUST
ADVERTISED DURATION	264°	264°
ACTUAL CAM LIFT (in/mm)	.350" / 8.89mm	.310" / 7.87mm
ROCKER ARM RATIO	1.75:1	1.75:1
CENTERLINE	106°	114°
LOBE SEPERATION	110°	
DURATION AT 0.050" CAM	187°	185°
DURATION AT 0.050" VALVE	203°	201°
VALVE CLEARANCE	.000" / 0mm HYDRAULIC	.000" / 0mm HYDRAULIC
RECOMMENDED SPRING KIT	BC0159 or BC0160	

CAMSHAFT TIMING AT 0.050" VALVE LIFT	OPEN	CLOSES
	INTAKE	4.5° ATDC
EXHAUST	34.5° BBDC	13.5° BTDC



NOTES

BC does not recommend using synthetic oil during break-in or operation. Follow OEM manufacturer's torque sequence and specifications. Use liberal amount of aftermarket engine assembly lube during installation. Check follower or bucket surfaces for abnormal wear and/or scuffing. On initial start-up and break-in run engine at 1500-2500 rpm for 20 minutes. **Camshafts damaged by improper installation, excessive spring pressure or retainers contacting valve guides or seals are void from warranty. Not legal for sale or use on emission controlled motor vehicles.**

